

Digital torquemeter SAUTER DB



Convenient way to test the torque of tools

Features

- **1** Particularly suitable for testing torque wrenches, electric hand screwdrivers and cordless screwdrivers
- **2 Torque pick-up system** for dynamic testing of electric screwdrivers (from SAUTER DB 0.5-4 to DB 50-2)
- **Metal housing** for continuous use in tough environmental conditions
- **Capacity display:** A bar lights up to show how much of the measuring range is still available.
- **LCD graphics display** with backlight
- **Rubber feet with anti-slip feature** at SAUTER DB 0.5-4 up to DB 10-3
- **3 Stable mounting plate** for solid fixation at SAUTER DB 20-3 up to DB 500-2
- **USB** and **RS-232** data interfaces included
- Scope of delivery: Torque pick-up, sturdy carry case, mounting plate (models with [Max] ≥ 20 Nm)
- **Internal data memory** saves up to 500 measurements. The memory contents can be transferred to the PC using optional software
- **Peak hold function** to capture the peak value or **Track-Funktion** for continuous display of measurement
- **Can be used in both directions of rotation**
- **Measuring with tolerance range (limit-setting function):** Upper and lower limiting can be programmed individually. The process is supported by an audible and visual signal
- **AUTO-OFF function**

Technical data

- Backlit LCD graphics display
- Units can be selected: Nm, lbf-in, kgf-cm, kgf-m, ft-lbf
- Measuring precision: ± 0,5 % of [Max]
- Measuring frequency: 1000 Hz
- Usable measuring range: 5–100 % of [Max]
- Overload protection: 150 % of [Max]
- Rechargeable battery pack integrated, standard, operating time up to 18 h without backlight, charging time approx. 14 h
- Overall dimensions W×D×H 200×100×50 mm
- Net weight approx. 3 kg

Accessories

- **Plug-In for data transfer of measuring data** from the measuring instrument and transfer to a PC, e.g. in Microsoft Excel®, SAUTER AFI-1.0
- **Force-time data transfer software** with graphic display of the measurement process, SAUTER AFH FAST
- **RS-232/PC connection cable** SAUTER FL-A04
- **USB/PC connection cable** SAUTER FL-A01

STANDARD





































OPTION



| Model | Measuring range [Max] Nm | Readout [d] Nm | Tool fitting mm/Inch | Option Factory calibration certificate | |
|-----------------|--------------------------------|----------------------|-------------------------|---|--|
| | | | | KERN | |
| SAUTER DB 0.5-4 | 0,5 | 0,0001 | 20 mm & 3/8" | 961-120 | |
| DB 1-4 | 1 | 0,0002 | 20 mm & 3/8" | 961-120 | |
| DB 5-3 | 5 | 0,001 | 20 mm & 3/8" | 961-120 | |
| DB 10-3 | 10 | 0,002 | 20 mm & 3/8" | 961-120 | |
| DB 20-3 | 20 | 0,005 | 20 mm & 3/8" | 961-120 | |
| DB 50-2 | 50 | 0,01 | 20 mm & 3/8" | 961-120 | |
| DB 100-2 | 100 | 0,02 | 3/8" | 961-120 | |
| DB 200-2 | 200 | 0,05 | 1/2" | 961-120 | |
| DB 500-2 | 500 | 0,05 | 3/4" | 961-120 | |

Pictograms

| | | |
|--|---|---|
|  Adjusting program (CAL): For quick setting of the instrument's accuracy. External adjusting weight required. |  Control outputs (optocoupler, digital I/O): to connect relays, signal lamps, valves, etc. |  ZERO: Resets the display to "0". |
|  Calibration block: standard for adjusting or correcting the measuring device. |  Analogue interface: to connect a suitable peripheral device for analogue processing of the measurements |  Battery operation: Ready for battery operation. The battery type is specified for each device. |
|  Peak hold function: capturing a peak value within a measuring process. |  Statistics: using the saved values, the device calculates statistical data, such as average value, standard deviation etc. |  Rechargeable battery pack: rechargeable set. |
|  Scan mode: continuous capture and display of measurements. |  PC Software: to transfer the measurement data from the device to a PC. |  Mains adapter: 230V/50Hz in standard version for EU. On request GB, AUS or USA version available. |
|  Push and Pull: the measuring device can capture tension and compression forces. |  Printer: a printer can be connected to the device to print out the measurement data. |  Power supply: Integrated, 230V/50Hz in EU. More standards e.g. GB, AUS or USA on request. |
|  Length measurement: captures the geometric dimensions of a test object or the movement during a test process. |  Network interface: For connecting the scale to an Ethernet network. |  Motorised drive: The mechanical movement is carried out by a electric motor. |
|  Focus function: increases the measuring accuracy of a device within a defined measuring range. |  KERN Communication Protocol (KCP): It is a standardized interface command set for KERN balances and other instruments, which allows retrieving and controlling all relevant parameters and functions of the device. KERN devices featuring KCP are thus easily integrated with computers, industrial controllers and other digital systems. |  Motorised drive: The mechanical movement is carried out by a synchronous motor (stepper). |
|  Internal memory: to save measurements in the device memory. | |  Fast-Move: the total length of travel can be covered by a single lever movement. |
|  Data interface RS-232: bidirectional, for connection of printer and PC. |  GLP/ISO record keeping: of measurement data with date, time and serial number. Only with SAUTER printers |  DAkkS calibration possible: The time required for DAkkS calibration is shown in days in the pictogram. |
|  Data interface USB: To connect the measuring instrument to a printer, PC or other peripheral devices. |  Measuring units: Weighing units can be switched to e.g. non-metric at the touch of a key. Please refer to website for more details. |  Factory calibration: The time required for factory calibration is specified in the pictogram. |
|  WLAN data interface: To transfer data from the balance to a printer, PC or other peripherals. |  Measuring with tolerance range (limit-setting function): Upper and lower limiting can be programmed individually. The process is supported by an audible or visual signal, see the relevant model |  Package shipment: The time required for internal shipping preparations is shown in days in the pictogram. |
|  Data interface Infrared: To transfer data from the measuring instrument to a printer, PC or other peripheral devices. | |  Pallet shipment: The time required for internal shipping preparations is shown in days in the pictogram. |

Your KERN specialist dealer: