

Stainless steel platform scale KERN SXS



Stainless steel platform scale with stainless steel IP68 display and EC type approval [M]



Piece counting



Recipe-weighing



Thanks to the stainless steel design of the housing and platform with smooth surface, the scale is rust-free and easy to clean

Stainless steel platform scale KERN SXS



Features

- Ideal for the robust industrial applications
- **1** Platform: made entirely of stainless steel, hermetically welded stainless steel load cell, protection against dust and water splashes IP68. Substruction in wing design, extremely resistant to bending. Earthed weighing plate, to reduce static charge
- Display device: stainless steel, dust and splash water protection IP68, integrated power supply
- Ideal for the increased hygienic requirements in the food industries
- Wall mount for display device, standard
- Superior display size: digit height 55 mm, bright backlight for easy reading of weighing results, even in poor lighting conditions
- Easy-to-use KERN menu structure with printout of weighing results which can be intuitively adapted
- Thanks to interfaces such as RS-232, RS-485 and Bluetooth (optional) the scale can easily be connected to existing networks and facilitates the data exchange between the scale and printer



Technical data

- Large backlit LCD display, digit height 55 mm
- Weighing plate dimensions, stainless steel
 - A** W×D×H 300×240×86 mm
 - B** W×D×H 400×300×89 mm
 - C** W×D×H 500×400×123 mm
 - D** W×D×H 650×500×133,5 mm
- Dimensions of display device W×D×H 232×150×80 mm
- Cable length of display device approx. 2,5 m
- Permissible ambient temperature -10 °C/40 °C



Accessories

- **2** Stand to elevate display device, for models with weighing plate size
 - A - D** Height of stand approx. 200 mm, KERN IXS-A02
 - B - D** Height of stand approx. 400 mm, KERN IXS-A03
 - C - D** Height of stand approx. 600 mm, KERN IXS-A04
- **3** Internal rechargeable battery pack, operating time up to 80 h without backlight, charging time approx. 12 h, must be ordered at purchase, KERN GAB-A04
- Foot switch, must be ordered at purchase, KERN XKS-A03
- Data interface RS-232, interface cable included, approx. 1,5 m, must be ordered at purchase, must be ordered at purchase, KERN XKS-A04
- Data interface RS-485, must be ordered at purchase, KERN XKS-A01
- Bluetooth data interface for wireless data transfer, must be ordered at purchase, not in combination with verification, KERN XKS-A02
- Further details, plenty of further accessories and suitable printers see *Accessories*

Note: It is only possible to install one cable option. Either KXS-A04, KXS-A01 or KXS-A03


STANDARD



OPTION



FACTORY



Model	Weighing capacity [Max] kg	Readability [d] g	Verification value [e] g	Minimal load [Min] g	Linearity g	Weighing plate	Verification	Option DAKKS Calibr. Certificate
High resolution readability								
SXS 6K-3	6	0,5	-	-	± 1,5	A	-	963-128
SXS 10K-3	15	1	-	-	± 3	A	-	963-128
SXS 10K-3L	15	1	-	-	± 3	B	-	963-128
SXS 30K-2	30	2	-	-	± 6	B	-	963-128
SXS 30K-2L	30	2	-	-	± 6	C	-	963-128
SXS 60K-2	60	5	-	-	± 15	B	-	963-129
SXS 60K-2L	60	5	-	-	± 15	C	-	963-129
SXS 100K-2	150	10	-	-	± 30	C	-	963-129
SXS 100K-2L	150	10	-	-	± 30	D	-	963-129
SXS 300K-2	300	20	-	-	± 60	D	-	963-129
Multi-range balance, with increasing load it switches automatically to the next largest weighing range [Max] and readout [d] and when the load is fully removed, the balance switches back to the lower range								
SXS 6K-3M	3 6	1 2	1 2	20 40	± 1 2	A	965-228	963-128
SXS 10K-3M	6 15	2 5	2 5	40 100	± 2 5	A	965-228	963-128
SXS 10K-3LM	6 15	2 5	2 5	40 100	± 2 5	B	965-228	963-128
SXS 30K-2M	15 30	5 10	5 10	100 200	± 5 10	B	965-228	963-128
SXS 30K-2LM	15 30	5 10	5 10	100 200	± 5 10	C	965-228	963-128
SXS 60K-2M	30 60	10 20	10 20	200 400	± 10 20	B	965-229	963-129
SXS 60K-2LM	30 60	10 20	10 20	200 400	± 10 20	C	965-229	963-129
SXS 100K-2M	60 150	20 50	20 50	400 1000	± 20 50	C	965-229	963-129
SXS 100K-2LM	60 150	20 50	20 50	400 1000	± 20 50	D	965-229	963-129
SXS 300K-2M	150 300	50 100	50 100	1000 2000	± 50 100	D	965-229	963-129

Note: For applications that require verification, please order verification at the same time, initial verification at a later date is not possible.

Verification at the factory, we need to know the full address of the location of use.

1 ONLY WHILE STOCKS LAST

- 
Internal adjusting:
 Quick setting up of the balance's accuracy with internal adjusting weight (motordriven)
- 
Adjusting program CAL:
 For quick setting up of the balance's accuracy. External adjusting weight required
- 
Easy Touch:
 Suitable for the connection, data transmission and control through PC or tablet.
- 
Memory:
 Balance memory capacity, e.g. for article data, weighing data, tare weights, PLU etc.
- 
Alibi memory:
 Secure, electronic archiving of weighing results, complying with the 2014/31/EU standard.
- 
KERN Universal Port (KUP):
 allows the connection of external KUP interface adapters, e.g. RS-232, RS-485, SB, Bluetooth, WLAN, Analogue, Ethernet etc. for the exchange of data and control commands, without installation effort
- 
Data interface RS-232:
 To connect the balance to a printer, PC or network
- 
RS-485 data interface:
 To connect the balance to a printer, PC or other peripherals. Suitable for data transfer over large distances. Network in bus topology is possible
- 
USB data interface:
 To connect the balance to a printer, PC or other peripherals
- 
Bluetooth* data interface:
 To transfer data from the balance to a printer, PC or other peripherals
- 
WiFi data interface:
 To transfer data from the balance to a printer, PC or other peripherals
- 
Control outputs (optocoupler, digital I/O):
 To connect relays, signal lamps, valves, etc.
- 
Analogue interface:
 to connect a suitable peripheral device for analogue processing of the measurements
- 
Interface for second balance:
 For direct connection of a second balance
- 
Network interface:
 For connecting the scale to an Ethernet network
- 
KERN Communication Protocol (KCP):
 It is a standardized interface command set for KERN balances and other instruments, which allows retrieving and controlling all relevant parameters and functions of the device. KERN devices featuring KCP are thus easily integrated with computers, industrial controllers and other digital systems
- 
GLP/ISO log:
 The balance displays weight, date and time, independent of a printer connection
- 
GLP/ISO log:
 With weight, date and time. Only with KERN printers.
- 
Piece counting:
 Reference quantities selectable. Display can be switched from piece to weight
- 
Recipe level A:
 The weights of the recipe ingredients can be added together and the total weight of the recipe can be printed out
- 
Recipe level B:
 Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through display
- 
Totalising level A:
 The weights of similar items can be added together and the total can be printed out
- 
Percentage determination:
 Determining the deviation in % from the target value (100 %)
- 
Weighing units:
 Can be switched to e.g. nonmetric units. See balance model. Please refer to KERN's website for more details
- 
Weighing with tolerance range:
 (Checkweighing) Upper and lower limiting can be programmed individually, e.g. for sorting and dosing. The process is supported by an audible or visual signal, see the relevant model
- 
Hold function:
 (Animal weighing program) When the weighing conditions are unstable, a stable weight is calculated as an average value
- 
Protection against dust and water splashes IPxx:
 The type of protection is shown in the pictogram.
- 
Suspended weighing:
 Load support with hook on the underside of the balance
- 
Battery operation:
 Ready for battery operation. The battery type is specified for each device
- 
Rechargeable battery pack:
 Rechargeable set
- 
Universal plug-in power supply:
 with universal input and optional input socket adapters for
 A) EU, CH, GB
 B) EU, CH, GB, USA
 C) EU, CH, GB, USA, AUS
- 
Plug-in power supply:
 230V/50Hz in standard version for EU, CH. On request GB, USA or AUS version available
- 
Integrated power supply unit:
 Integrated in balance. 230V/50Hz standard EU. More standards e.g. GB, USA or AUS on request
- 
Weighing principle: Strain gauges
 Electrical resistor on an elastic deforming body
- 
Weighing principle: Tuning fork
 A resonating body is electromagnetically excited, causing it to oscillate
- 
Weighing principle: Electromagnetic force compensation
 Coil inside a permanent magnet. For the most accurate weighings
- 
Weighing principle: Single cell technology:
 Advanced version of the force compensation principle with the highest level of precision
- 
Verification possible:
 The time required for verification is specified in the pictogram
- 
DAkkS calibration possible (DKD):
 The time required for DAkkS calibration is shown in days in the pictogram
- 
Factory calibration (ISO):
 The time required for Factory calibration is shown in days in the pictogram
- 
Package shipment:
 The time required for internal shipping preparations is shown in days in the pictogram
- 
Pallet shipment:
 The time required for internal shipping preparations is shown in days in the pictogram

*The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by KERN & SOHN GmbH is under license. Other trademarks and trade names are those of their respective owners.